



UL410 (SA34033) matte anti-slip pressure sensitive lamination film with liner

This PVC textured laminate was specially designed to be a protective overlay for virtually any substrate with high tack adhesive to create a temporary Floor advertisement. Formulated solvent acrylic adhesive for a strong bond and exceptional clarity. UL rated (UL410 SA34033) for anti-slip properties.



Benefits:

- UL Anti Slip Rated (UL410 SA34033)
- Economical
- Ultra Clear Visibility

Applications:

- Short Term Interior Floors
- Floor & Counter Top Advertising
- Sealed Concrete Floor Graphics



TECHNICAL DATA: UL410 (SA34033) MATTE ANTI-SLIP PRESSURE SENSITIVE LAMINATION FILM WITH LINER

| | | | |
|--------------------|-----------------------------|----------------------|--|
| SURFACE FINISH: | Textured | FACE STOCK CALIPER: | 8 Mil +/- 1 |
| BASE MATERIAL: | PVC | DURABILITY: | Indoor: Up to 1 year Outdoor: Up to 6 months |
| ADHESIVE MATERIAL: | Permanent Solvent Acrylic | ROLL LENGTH: | 150 Ft. |
| LINER MATERIAL: | Kraft w/PE Coating One Side | ROLL WIDTHS: | 38" & 54" |
| LINER WEIGHT: | 80 GSM +/- 10% | CORE: | 3" |
| LINER CALIPER: | 4 +/- 1 Mil | PRINT SIDE: | Print Side Out |
| FACE STOCK WEIGHT: | 200 GSM +/- 10% | INK RECOMMENDATIONS: | N/A |

STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°)



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)