



## Satin pressure sensitive lamination film with liner

Everyday pressure sensitive laminate with “cold” permanent adhesive. The 4 mil PVC base works well with almost any media type, unlike heat-assisted laminates.



### Benefits:

- Ultra Clear Visibility
- Waterproof
- Protects Graphics
- Neutral Smooth Satin Finish

### Applications:

- Indoor Signage
- High Traffic Advertising
- Short Term Outdoor Signage
- Menus

#### TECHNICAL DATA: SATIN PRESSURE SENSITIVE LAMINATION FILM WITH LINER

|   |                              |                     |  |
|---|------------------------------|---------------------|--|
| SURFACE FINISH:   | Satin                        | FACE STOCK CALIPER: | 4 Mil +/- 1                                  |
| BASE MATERIAL:  | PVC                          | DURABILITY:         | Indoor: Up to 1 year Outdoor: Up to 6 months |
| ADHESIVE MATERIAL:  | Permanent Solvent Acrylic    | ROLL LENGTH:        | 150 Ft.                                      |
| LINER MATERIAL:   | Kraft w/ PE Coating One Side | ROLL WIDTHS:        | 38", 43", 51", 54", & 61"                    |
| LINER WEIGHT:   | 80 GSM +/- 10%               | CORE:               | 3"   |
| LINER CALIPER:  | 4 +/- 1 Mil                  | PRINT SIDE:         | Print Side Out                               |
| FACE STOCK WEIGHT:  | 105 GSM +/- 10%              | INK RECOMENDATIONS: | N/A  |
| STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°) |                              |                     |  |



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)