



Matte WR instant dry Tyvek.

Tyvek by Dupont is a durable, tear resistant, and extremely light weight. Smooth print side with our microporous receptive coating allows for heavy ink loads while maintaining sharp resolution. Our top coating is specifically formulated for high speed print systems and has been tested and approved for the HP Pagewide XL series. Super fast dry times to keep up with heavy production.






Benefits:

- Smooth Non Glare Finish
- Durable & Strong
- Smudge Resistant
- Easy To Handle Lightweight

Applications:

- Posters & Presentations
- Lightweight Banners
- Trade Show & Event Displays
- POP & Retail Display

TECHNICAL DATA: MATTE WR INSTANT DRY TYVEK

SURFACE FINISH:	Matte	OPACITY:	92
BASE MATERIAL:	Dupont Tyvek	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
BASE WEIGHT:	70 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER:	8 Mil +/- 1	ROLL WIDTHS:	36"
BRIGHTNESS:	103 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	138 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT:	2 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	 AQUEOUS  LATEX  UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)