



QM-AMG: Professional Gloss Microporous High Performance Polyester Film

This elite polyester is one of our highest performing film banner materials. It's superior curl resistance and tear resistance with its microporous coating gives it the ability to reproduce photo quality images and make this the ideal media for indoor signage. Requires no lamination unless higher protection is needed.






Benefits:

- Curl Resistant
- Water Resistant/Tear Resistant
- High Resolution
- High Black Density
- High Scratch Resistance

Applications:

- POP Display
- Indoor Banners
- Photo Reproduction
- Short Term Outdoor Banners
- Poster Production

TECHNICAL DATA: QM-AMG – PROFESSIONAL GLOSS MICROPOROUS HIGH PERFORMANCE POLYESTER FILM

SURFACE FINISH:	Gloss	OPACITY:	97
BASE MATERIAL:	PET	DURABILITY:	Indoor: Up to 2 years Outdoor: Up to 6 months
BASE WEIGHT:	265 GSM +/- 10%	ROLL LENGTH:	200 FT.
CALIPER:	8 mil +/- 1	ROLL WIDTHS:	36"
BRIGHTNESS:	107 (ISO Blue Whiteness R457)	CORE:	3" with 2" Adapter
WHITENESS:	97 (CIE Ganz)	PRINT SIDE:	Print Side Out
GLOSS MEASUREMENT:	60 +/- 10% by angle of 60°	INK RECOMENDATIONS:	 AQUEOUS  LATEX  UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)