



QM-SGV6: Thick gloss vinyl w/ permanent adhesive

SGV6 is your best option for easy application. It's bright white surface provides the best color graphics and it's improved double-side PE coated liner makes for easy installations. The solvent acrylic adhesive provides longer term adhesion. This product is sure to be your go-to for most mounted jobs.



Benefits:

- Bright White
- High Gloss
- Easy Application

Applications:

- Decals
- Flexible or Mounted Signage
- Trade Show Graphics

Registered Latex Developer

TECHNICAL DATA: QM-SGV6 – THICK GLOSS VINYL W/ PERMANENT ADHESIVE

SURFACE FINISH:	Gloss	WHITENESS:	145 (CIE Ganz)
BASE MATERIAL:	PVC	OPACITY:	97
ADHESIVE MATERIAL:	Clear solvent acrylic PSA	GLOSS MEASUREMENT:	28 +/- 10% by angle of 60°
LINER MATERIAL:	Double-side PE coated white Wood-pulp Paper	DURABILITY:	<i>Indoor:</i> Up to 1 year <i>Outdoor:</i> Up to 6 months
LINER WEIGHT:	160 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	6 Mil +/- 1	ROLL WIDTHS:	54"
FACE STOCK WEIGHT:	210 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	6 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	96 (ISO Blue Whiteness):	INK RECOMENDATIONS:	ECO-SOLVENT LATEX UV
STORAGE:	Up to six months if stored in proper conditions (cool, dry place 50-80°)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)