



QM-TASQUE:

Matte anti-slip "1-Step" vinyl w/ high tac adhesive
UL410 (SA34033)

This is our award winning, budget friendly "1-Step" floor graphic vinyl that can be used on just about any smooth surface. It helps businesses maximize their advertising space by adding floor graphics in high traffic areas at a reasonable cost. Can also be used on counter tops, sealed concrete, and mounted to boards.



Benefits:

- Economical Floor Solution
- Easy to Apply
- UL 410 Slip Resistance
- High Tack Removable

Applications:

- Interior Floors
- Counter Displays
- Table Top Graphics
- Low Pile Carpet

Registered Latex Developer



TECHNICAL DATA: MATTE ANTI-SLIP WHITE VINYL W/ HIGH TAC ADHESIVE UL410 (SA34033)

SURFACE FINISH:	Matte Textured	OPACITY:	98
BASE MATERIAL:	PVC Vinyl	GLOSS MEASUREMENT:	5 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	Solvent/Acrylic High Tac Removable Adhesive	DURABILITY:	*Indoor: Up to 3 months depending on traffic. *Outdoor: Up to 60 days depending on traffic and weather.
LINER MATERIAL:	Coated PE Paper	STORAGE:	Up to 1 year if stored in proper conditions (cool, dry place 50-80°)
LINER WEIGHT:	120 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	7 Mil +/- 1	ROLL WIDTHS:	38", 54" & 60"
FACE STOCK WEIGHT:	260 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	8 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	90 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV
WHITENESS:	105 (CIE Ganz)		

*Surface must be cleaned before installation, all loose debris removed from surface. For best results, apply with a rubber roller to ensure edges are sealed and water cannot get under graphic



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

