



QM-POLCAN: Archival grade matte WR coated polyester/ cotton canvas

An exceptional museum grade canvas for the most discerning printer. Compare our canvas to any competitive matte canvas and you will find that it's an OBA-Free coating, along with bright white point translates to a true archival, acid-free print production. The matte receptive coating allows for heavy ink loads providing wide color gamut, high black DMAX, and rich skin tones. Finish this canvas off with liquid laminate for crack-free gallery wrapping.



Benefits:

- 35% Cotton/65% Polyester
- Anti-Sag Weave
- True Archival
- OBA Free Coating
- Matte Finish




Applications:

- Museum And Gallery Prints
- Home Décor Printing
- Photo Reproduction
- Gallery Stretched Giclee's
- Framed Art

Registered Latex Developer



TECHNICAL DATA: ARCHIVAL GRADE MATTE WR COATED POLYESTER/COTTON CANVAS

SURFACE FINISH:	Matte	OPACITY:	96
BASE MATERIAL:	35% cotton 65% polyester	DURABILITY:	Indoor: 25 years+ Outdoor: 6 months
WEAVE:	2:1 Oxford	ROLL LENGTH:	45 FT.
BASE WEIGHT:	420 GSM +/- 10%	ROLL WIDTHS:	24", 36", 44" & 60"
CALIPER:	21 Mil +/- 2	CORE:	3" with 2" adapter
BRIGHTNESS:	82 (ISO Blue Whiteness)	PRINT SIDE:	Print Side Out
WHITENESS:	79 (CIE Ganz)	INK RECOMMENDATIONS:	 AQUEOUS  LATEX  UV
GLOSS MEASUREMENT:	3 +/- 10% by angle of 60°		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

