



Magnate

Eco Solvent, Latex, UV Media



QM-TRUEVIEW: Optically clear PET with removable adhesive

This unique, optically clear, PVC-free, adhesive film is perfect for edge to edge store front window applications and also ideal for contour-cut window graphics. This rigid media combined with silicone-based removable adhesive allows for very easy repositioning and removal. Perfect for restaurants, bars and retail window advertising!

For best optical results, we recommend wet installation.



Benefits:

- Optically Clear for Glass and Plexiglass
- Simulate Cut Vinyl
- Easy to Install
- Scratch Resistant Coating
- PVC-free

Applications:

- Edge to Edge Windows
- Contour Cut
- Store Front Glass, Plexi Dividers Display Cases, Kiosks
- Any smooth surface
- Decor Printing

Quick Reference: Common retail glass & window widths for edge-to-edge applications.

7-Eleven	Beyond Food Mart	Am-Pm Store	Albertsons	Ralphs
Cooler Door 27"	Cooler Door - 31"	Cooler Door - 25"	Cooler Door 27"	Cooler Door 27"
Outside Window 34"	Outside Window - 33"	Outside Window - 48"	Outside Window - 65"	Outside Window - 60"

Registered Latex Developer



TECHNICAL DATA: OPTICALLY CLEAR PET WITH REMOVABLE ADHESIVE

SURFACE FINISH:	Gloss	WHITENESS:	29 (CIE Ganz)
BASE MATERIAL:	Polyester Film	OPACITY:	0
ADHESIVE MATERIAL:	Optically Clear Removable Silicone	GLOSS MEASUREMENT:	98 +/- 10% by angle of 60°
LINER MATERIAL:	Frosted PET	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
LINER WEIGHT:	70 GSM +/- 10%	ROLL LENGTH:	100 Ft.
LINER CALIPER:	2 Mil +/- .5	ROLL WIDTHS:	50"
FACE STOCK WEIGHT:	185 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	6 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	40 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

