



QM-SWRPPBO2S 2-sided blackout matte polypropylene

Double-sided bright white matte top coated with blackout to produce colorful 2-sided printing. The perfect solution for trade show displays, posters, double sided window graphics, and snap-in sign stands requiring two-way traffic.



Benefits:

- 2-Sided Printing
- Durable Composition
- Blockout
- Instant Dry Coating
- Scratch Resistant
- Tear Resistant
- Water Resistant
- Curl Resistant

Applications:

- Low Cost Roll-Up Displays
- Banner Stands
- POP-IN Displays
- Sign Stands
- "Push-Pull" Window Graphics
- Trade Show Displays
- Hanging Signs

Registered Latex Developer



TECHNICAL DATA: 2-SIDED BLOCKOUT MATTE POLYPROPYLENE

SURFACE FINISH:	Matte/Matte	OPACITY:	99
BASE MATERIAL:	Polypropylene	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months
BASE WEIGHT:	220 GSM +/- 10%	ROLL LENGTH:	100 FT.
CALIPER:	11 Mil +/- 1	ROLL WIDTHS:	36" & 60"
BRIGHTNESS:	90 (ISO Blue Whiteness)	CORE:	3"
WHITENESS:	93 (CIE Ganz)	PRINT SIDE:	Both Sides
GLOSS MEASUREMENT	13 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	ECOSOLVENT LATEX UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

