



Zoom Board™ QM-2436VPWM:
Matte rigid microporous inkjet compatible board w/anti-slip backside.

Ideal for flatbed print systems, *Zoom Board™* is a great solution for countless graphic displays that demand a rigid, durable print media. Its microporous surface accepts Aqueous, Latex and UV ink-sets.



Benefits:

- Rigid .8MM Thick
- Anti-slip Backside
- Durable Corners/Edges
- Water Resistant
- Can be cut, drilled and grommetted

Applications:

- Stand-alone Signage
- Hanging Signage
- Yard Signage
- Easel Displays
- Cue Cards
- Drop-in Sign Frames

Registered Latex Developer

TECHNICAL DATA: MATTE 8MM RIGID MICROPOROUS INKJET COMPATIBLE BOARD W/ANTI-SLIP BACKSIDE

SURFACE FINISH:	Matte	OPACITY:	100
SURFACE MATERIAL:	Polypropylene	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
THICKNESS:	.8MM	SHEET SIZES:	24" x 36"
BRIGHTNESS:	108 (ISO Blue Whiteness)	SHEETS PER BOX	50
WHITENESS	125 (CIE Ganz)	PRINT SIDE:	Single Side Print
GLOSS MEASUREMENT:	3 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	AQUEOUS LATEX UV



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

