



WIDE FORMAT &
DIGITAL PRINT MEDIA

Marquis
Digital/Laser Print Media

Midas
Latex Media



QM-TRITEXT7: Satin Hybrid Media

(Available in sheets and wide format rolls)

A very unique product. Slightly softer than polypropylene, but has much more strength and durability, virtually tear-proof. The most economical alternative to Tyvek, Teslin, and other tear strength products, that also works with multiple print platforms. This tree-free and PVC-free media truly redefines film with many various applications that require extreme durability.

Benefits:

- Tear Resistant
- Water/Weather Resistant
- Light Weight
- Can be written on with pen, pencil, or sharpie

Applications:

- Wristbands
- Placemats
- Banners, Signs, & Posters
- Maps, Guides, & Blueprints
- Runners Bibs

Registered Latex Developer



TECHNICAL DATA:

SURFACE FINISH:	Satin	OPACITY:	96
MELTING POINT:	390° F	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months SHEET
BASE WEIGHT:	140 GSM +/- 10%	SIZES:	12 x18 in. 13 x19 in. (Special order sizes available.)
CALIPER:	7 MIL +/- 1	ROLL WIDTHS:	36" 60"
BRIGHTNESS:	101 (ISO Blue Whiteness)	ROLL LENGTH:	200 FT.
WHITENESS	123 (CIE Ganz)	PRINT SIDE:	Double Side Printable
GLOSS MEASUREMENT:	6 +/- 10% by angle of 60°	INK RECOMMENDATIONS:	ECO-SOLVENT LATEX COLOR LASER INDIGO DIGITAL PRESS UV KIP



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

