



Magnate

Eco Solvent, Latex, UV Media



QM-ECOWV:

Perforated vinyl 70/30 ratio w/ removable adhesive dual paper liner

The 70/30% perforation pattern allows for the maximum print surface, making it ideal for all retail exterior-mount window graphics requiring small detail and text. Clear adhesive, removable up to one year. The dual perforated paper liner protects printer beds.



Hole Size: 1.6mm, Perf Ratio of 30%



Benefits:

- Easy Application
- Removable
- Vivid Graphics

Applications:

- POP Decals
- Retail and Commercial Window Signage

Registered Latex Developer



TECHNICAL DATA: PERFORATED VINYL 70/30 RATIO W/ REMOVABLE ADHESIVE DUAL PAPER LINER

SURFACE FINISH:	Gloss	BRIGHTNESS:	74 (ISO Blue Whiteness)
BASE MATERIAL:	PVC	WHITENESS:	80 (CIE Ganz)
BASE SIDE DESCRIPTION:	White Surface/Black Back	GLOSS MEASUREMENT:	46 +/- 10 by angle of 60°
ADHESIVE MATERIAL:	Solvent PSA	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
LINER MATERIAL:	Perforated Silicon and PE Coating Composit Liner	ROLL LENGTH:	164 Ft.
LINER WEIGHT:	185 GSM +/- 10%	ROLL WIDTHS:	54"
LINER CALIPER:	10 Mil +/- 1	CORE:	3"
FACE STOCK WEIGHT:	167 GSM +/- 10%	PRINT SIDE:	Print Side Out
FACE STOCK CALIPER:	7 Mil +/- 1	INK RECOMMENDATIONS:	ECO-SOLVENT LATEX UV
STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°)			

**Accepts a maximum of 200% ink flow for UV print systems*



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

