



QM-SPP2P 2 Mil Metalized Polypropylene w/White Liner

This unique highly reflective mirror-like polypropylene comes with a durable permanent adhesive, making it a fantastic choice for any high end retail labelling application. This paper-free and PVC-free media truly redefines standard adhesive film media, providing extreme durability and the added benefit of performing great for die-cutting. Compatible with Dry Toner, Indigo, Digital Press, and all UV printing platforms.



Benefits:

- Highly Reflective Mirror-Like Finish
- Water & Tear Resistant
- Die-cut & Perforation Friendly
- Compliments White Toner/Ink Printing

Applications:

- Die-cut Labels & Seals
- Bottle & Cans
- Decorative Labelling
- Retail/Lab/Shop Labelling
- Stickers/Decals



Registered Latex Developer



TECHNICAL DATA: METALIZED POLYPROPYLENE W/CCK WHITE LINER			
SURFACE FINISH:	Highly Reflective Metallic	WHITENESS	N/A (CIE Ganz)
ADHESIVE TYPE:	Permanent Acrylic	GLOSS MEASUREMENT:	99 +/- 10% by angle of 60°
MELTING POINT:	390° F	OPACITY:	96
FACE STOCK WEIGHT:	46 GSM +/- 10%	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
FACE STOCK CALIPER:	2 MIL +/- 1	SHEET SIZES:	8.5 x 11", 8.5 x 14", 11 x 17", 12 x18", 13 x 19"
LINER WEIGHT:	130 GSM +/- 10%	PRINT SIDE:	Single Side Printable
LINER CALIPER:	5 MIL +/- 1	INK RECOMMENDATIONS:	COLOR LASER, INDIGO, DIGITAL PRESS, UV
BRIGHTNESS:	N/A (ISO Blue Whiteness)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

