



QM-SPPMP: Matte Blockout Polypropylene with Permanent Adhesive

Developed as a long lasting, tear resistant, shrink resistant alternative to traditional PVC Vinyl adhesive products. Equipped with blockout and a solvent acrylic permanent adhesive, makes it a perfect choice for rigid board signage, long lasting contour cut stickers, and other labeling applications. Economical and PVC-Free, this product is excellent alternative to the more expensive polymeric adhesive vinyls on the market.



Benefits:

- PVC-Free
- Curl Resistant
- Longer Lasting than Monomeric PVC
- Blockout
- Matte Finish, Better Image Clarity
- More Economical than Barrier Film

Applications:

- Rigid Board Signage
- Packaging Labels
- Event Graphics
- Durable Permanent Label Application
- Barrier Film Replacement Product

Registered Latex Developer



TECHNICAL DATA:

SURFACE FINISH:	Matte	OPACITY:	99%
BASE MATERIAL:	Polypropylene	GLOSS MEASUREMENT:	9 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	Permanant Adhesive	DURABILITY:	Indoor: Up to 1 year. Outdoor: Up to 6 months
LINER MATERIAL:	Clear Polypropylene	STORAGE:	Up to 1 year if stored in proper conditions (cool, dry place 50-80°)
LINER WEIGHT:	60 GSM +/- 10%	ROLL LENGTH:	100 Ft.
LINER CALIPER:	2 Mil +/- 1	ROLL WIDTHS:	54"
FACE STOCK WEIGHT:	230 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	7 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	91 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV
WHITENESS:	112 (CIE Ganz)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

