



## QM-GLASSTACMED: Satin Hybrid Media w/ Removable Adhesive

Vibrant colors and sharp line printing make this media stand out from the crowd. The most economical alternative to Tyvek, Teslin, and other tear strength products, that also works with multiple print platforms. This tree free and PVC free media truly redefines film with many various applications that require extreme durability and/or die cutting. The removable adhesive makes it easy to switch out with no residue.



### Benefits:

- Tear Resistant & Leaves No Residue
- Water/Weather Resistant
- Lightweight & Stretch Resistant
- Can be written on with pen, pencil, or sharpie

### Applications:

- Window Clings
- Stickers & Decals
- Banners, Signs, & Posters
- Cooler Door Stickers

Registered Latex Developer



### TECHNICAL DATA: SATIN HYBRID MEDIA W/ REMOVABLE ADHESIVE

SURFACE FINISH:	Satin	WHITENESS	97 (CIE Ganz)
ADHESIVE TYPE:	Removable Acrylic	GLOSS MEASUREMENT:	7 +/- 10% by angle of 60°
MELTING POINT:	390° F	OPACITY:	98
FACE STOCK WEIGHT:	188 GSM +/- 10%	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
FACE STOCK CALIPER:	9 MIL +/- 1	SHEET SIZES:	8.5 x 11", 8.5 x 14", 11 x 17", 12 x 18", 13 x 19"
LINER WEIGHT:	109 GSM +/- 10%	PRINT SIDE:	Single Side Printable
LINER CALIPER:	4 MIL +/- 1	INK RECOMMENDATIONS:	COLOR LASER, INDIGO, DIGITAL PRESS, UV
BRIGHTNESS:	99 (ISO Blue Whiteness)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

