



QM-MOTOPRINT: Gloss Polymeric PVC Vinyl with High Tack Permanent Air Egress Adhesive

Developed as a long lasting, polymeric, shrink resistant PVC vinyl for high end vehicle decals and signage. Equipped with a one of a kind high tack, marine-grade, air-egress permanent adhesive, this product is a perfect choice for motorcycle sticker kits, long lasting contour cut stickers, and other labeling applications. Originally designed to cater to the most demanding motorcycle, snow mobile, or quad OEM graphic kits, this product is also a great choice for 2+ year durable outdoor signage. When the application calls for an extremely aggressive adhesive to withstand freezing temperatures, or high heat, this unique adhesive PVC vinyl has been developed for extreme durability and long life span. Rather than using extremely expensive cast vinyl for long lasting stickers/signage, consider adding this durable PVC adhesive product to your customer's print shop.

Benefits:

- Polymeric PVC Vinyl
- High Tack Air-Egress Permanent Adhesive
- Longer Lasting than Monomeric PVC
- Economical Price
- Stay Flat PE-Coated Paper liner

Applications:

- Vehicle Sticker Kits
- Long Lasting Labels
- Event Graphics
- Durable Permanent Adhesive PVC Applications

TECHNICAL DATA:

SURFACE FINISH:	Gloss	OPACITY:	97
BASE MATERIAL:	Polymeric PVC Vinyl	GLOSS MEASUREMENT:	53 +/- 10% by angle of 60°
ADHESIVE MATERIAL:	High Tack Marine Grade Permanent	DURABILITY:	*Indoor: Up to 3 years. Outdoor: Up to 2 years
LINER MATERIAL:	PE Coated Air-Egress	STORAGE:	Up to 1 year if stored in proper conditions (cool, dry place 50-80°)
LINER WEIGHT:	160 GSM +/- 10%	ROLL LENGTH:	150 Ft.
LINER CALIPER:	3.2 Mil +/- 1	ROLL WIDTHS:	54"
FACE STOCK WEIGHT:	150 GSM +/- 10%	CORE:	3"
FACE STOCK CALIPER:	3.2 Mil +/- 1	PRINT SIDE:	Print Side Out
BRIGHTNESS:	91 (ISO Blue Whiteness)	INK RECOMMENDATIONS:	ES ECO-SOLVENT L LATEX UV UV
WHITENESS:	123 (CIE Ganz)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

