



### QM-GPP2P:

#### 2 Mil Polypropylene Gloss White w/CCK White Liner

This gloss finished polypropylene film provides a durable, adhesive label solution that is tear/water resistant. This tree-free and PVC-free media truly redefines film with many various applications that require extreme durability and/or die cutting. The permanent adhesive makes it great for long lasting graphics that stay put. Accepts UV, Dry Toner, Indigo and Digital Press print systems.



#### Benefits:

- Water & Tear Resistant
- Permanent Adhesive
- Die-cut Friendly
- Dimensionally Stable

#### Applications:

- High Moisture Areas
- Cooler Door Advertising
- Stickers & Decals
- Labels



Registered Latex Developer



#### TECHNICAL DATA:

SURFACE FINISH:	Gloss	WHITENESS	123 (CIE Ganz)
ADHESIVE TYPE:	Permanent Acrylic	GLOSS MEASUREMENT:	20 +/- 10% by angle of 60°
MELTING POINT:	390° F	OPACITY:	96
FACE STOCK WEIGHT:	50 GSM +/- 10%	DURABILITY:	Indoor: Up to 1 year Outdoor: Up to 6 months
FACE STOCK CALIPER:	2 MIL +/- 1	SHEET SIZES:	8.5 x 11", 8.5 x 14", 11 x 17", 12 x 18", 13 x 19"
LINER WEIGHT:	130 GSM +/- 10%	PRINT SIDE:	Single Side Printable
LINER CALIPER:	5 MIL +/- 1	INK RECOMMENDATIONS:	COLOR LASER, INDIGO, DIGITAL PRESS, UV
BRIGHTNESS:	101 (ISO Blue Whiteness)		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to one year if stored in proper conditions (cool, dry place 50-80°)

