

WIDE FORMAT & DIGITAL PRINT MEDIA





QM-LX13M: 13 oz. matte frontlit fire retardant scrim banner

Unlike most scrim banner on the market, this banner media was developed to be extremely durable and work across Latex, EcoSolvent, and UV platforms. Its high tensile strength 1000 x 1000 denier scrim, makes for a very tear resistant banner. The fire retardant coating allows it to be used in all environments.



Benefits:

- Fire Retardant
- 1000 x 1000 Denier
- Durable and Tear Resistant
- Polyester & PVC Composition
- Non Glare Matte Finish

Applications:

- Frontlit Banners
- Display Systems
- Grommeted Signage
- Outdoor Signage
- Hanging Banners

Registered Latex Developer

TECHNICAL DATA:				
SURFACE FINISH:	Matte	OPACITY:	100	
BASE MATERIAL:	PVC	DURABILITY:	Indoor: Up to 1 year Outdoor: 6 months	
BASE WEIGHT:	(13 oz.) 440 GSM +/- 10%	ROLL LENGTH:	150 FT.	
DENIER:	1000D × 1000D	ROLL WIDTHS:	38", 54" & 60"	
CALIPER:	15 Mil +/- 1	CORE:	3″	
BRIGHTNESS:	85 (ISO Blue Whiteness)	PRINT SIDE:	Print Side Out	
WHITENESS:	116 (CIE Ganz)	INK RECOMMENDATIONS:	💩 ECO-SOLVENT 🐧 LATEX 💩 UV	
GLOSS MEASUREMENT	6 +/- 10% by angle of 60°	STORAGE: Up to six months if	STORAGE: Up to six months if stored in proper conditions (cool, dry place 50-80°)	



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

