



**WIDE FORMAT &
DIGITAL PRINT MEDIA**

Millennium
Laminates & Adhesives



QM-LAM8TAS:

UL410 (SA34033) matte anti-slip pressure sensitive lamination film with liner

This PVC textured laminate was specially designed to be a protective overlay for virtually any substrate with high tack adhesive to create a temporary Floor advertisement. Formulated solvent acrylic adhesive for a strong bond and exceptional clarity. UL rated (UL410 SA34033) for anti-slip properties.



Benefits:

- UL Anti Slip Rated (UL410 SA34033)
- Economical
- Ultra Clear Visibility

Applications:

- Short Term Interior Floors
- Floor & Counter Top Advertising
- Sealed Concrete Floor Graphics



TECHNICAL DATA:

SURFACE FINISH:	Textured	FACE STOCK CALIPER:	8 Mil +/- 1
BASE MATERIAL:	Monomeric PVC	DURABILITY:	Expected outdoor exposure is 1 year+ under normal conditions
ADHESIVE MATERIAL:	Permanent Solvent Acrylic	ROLL LENGTH:	150 Ft.
LINER MATERIAL:	Kraft w/PE Coating One Side	ROLL WIDTHS:	38" & 54"
LINER WEIGHT:	80 GSM +/- 10%	CORE:	3"
LINER CALIPER:	4 +/- 1 Mil	PRINT SIDE:	Print Side Out
FACE STOCK WEIGHT:	200 GSM +/- 10%	INK RECOMMENDATIONS:	N/A
STORAGE LIFE:	Up to 1-year shelf life when stored at 70°F and 50% relative humidity		



This media is designed for digital printing applications using OEM printers with their accompanying OEM ink sets. Although designed for all printers using the aforementioned OEM matching ink sets; actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F ±5°F and relative humidity of 50% RH ±3% RH. Our wide format media is guaranteed against manufacturing flaws and defects and is designed to resist printer jams when used properly. Storage: Up to six months if stored in proper conditions (cool, dry place 50-80°)

